

# ARVEN

Incassi / Recess spotlights



2006/95/CE -- 2002/95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1 -- EN 62471 -- EN 62031

## Applicazione

Soffitto / Parete


Faro da incasso con 1 led da 1W.  
Corpo in lega di alluminio e flangia in PMMA.  
Installazione a soffitto o parete con molle o con apposita controcassa.  
Fornito con 150mm di cavo 2x0,35.  
Unità di alimentazione non compresa.

## Application




Ceiling / wall

Recessed spotlight with 1x1W LED  
Aluminum alloy body with PMMA flange.  
Ceiling or wall installation with springs or outer casing provided  
Provided with 150mm of 2x0.35 cable  
Power supply unit not included

KELVIN	CRI	LUMEN NOMINALE 85° / NOMINAL LUMEN 85°	LUMEN EFFETTIVI / REAL OUTPUT
3000	80	113	~ 63
6000 4000	80	118	~ 66



## Arven



### INCLUDED



Codice/Cod: **3123**




FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round <b>10</b>	PMMA <b>0</b>	6000 K <b>1</b>	Diffused <b>0</b>
Quadrato / Square <b>20</b>		4000 K <b>2</b>	
		3000 K <b>3</b>	

350mA **IP 40** EN 60598 2-2

### ACCESSORI / ACCESSORIES

305000001	Controcassa / Outer casing
330001900	Alimentatore per max 4pz / Power supply for max 4 pcs
330002000	Alimentatore per min 4pz - max 12pz / Power supply for 4-12 pcs

## Arven IP44



### INCLUDED



Codice/Cod: **3165**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round <b>10</b>	PMMA <b>0</b>	6000 K <b>1</b>	Diffused <b>0</b>
Quadrato / Square <b>20</b>		4000 K <b>2</b>	
		3000 K <b>3</b>	

350mA **IP 44** EN 60598 2-2

### ACCESSORI / ACCESSORIES

305000001	Controcassa / Outer casing
330001900	Alimentatore per max 4pz / Power supply for max 4 pcs
330002000	Alimentatore per min 4pz - max 12pz / Power supply for 4-12 pcs