

NARON RGB

Incassi calpestabili / Recess walk-over spotlights



2006/95/CE -- 2002/95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1 -- EN 62471 -- EN 62031

Applicazione

Soffitto / Parete / Pavimento

Faro da incasso calpestabile IP66 - IK10 con 6 led da 1W RGB.

Corpo in lega di alluminio e flangia in PMMA.

Installazione a soffitto, parete o pavimento con molle o con apposita controcassa.

Fornito con 1m di cavo neoprene 6X0,5mm".

Unità di alimentazione non compresa.

Application

Ceiling / wall / floor

Recessed walk-over spotlight RGB IP66 - IK10 with 6x1.7W LEDs

Aluminum alloy body with PMMA flange.



Ceiling, wall or floor installation with springs or special casing

Provided with 1m of 6x0.5 Neoprene cable

Power supply unit not included



Naron RGB 6W versione con molle / with springs



Codice/Cod: **3157**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round 10	PMMA 0	RGB 9	Diffused 0
Quadrato / Square 20			

350mA



EN 60598 2-2

ACCESSORI / ACCESSORIES

330004800	Centralina PUSH per max 4pz / PUSH control unit for max 4pcs
307500013	Cavo neoprene 6x0,5mm". / Neoprene cable 6x0.5