

# NARON FLAT SURFACE

Incassi calpestabili / Recess walk-over spotlights

2006/95/CE -- 2002/95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1 -- EN 62471 -- EN 62031



## Applicazione

Soffitto / Parete / Pavimento

Faro da incasso calpestabile IP66 - IK10 con 1 led da 1,7W.

Corpo in lega di alluminio e flangia in PMMA.

Installazione a soffitto, parete o pavimento con apposita controcassa.

Fornito con 1m di cavo neoprene 2x0,5.

Unità di alimentazione non compresa.

## Application

Ceiling / wall / floor

Recessed walk-over spotlight IP66 - IK10 with 1x1.7W LED

Aluminum alloy body with PMMA flange.

Ceiling, wall or floor installation with outer casing provided


Provided with 1m of 2x0.5 Neoprene cable

Power supply unit not included

KELVIN	CRI	LUMEN EFFETTIVI / REAL OUTPUT
2700	90	~ 85
3000	90	~ 110
4000	75	~ 115
5000		



## Naron flat surface 1,7W



### INCLUDED



Codice/Cod: **3158**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Raso / Trimless	PMMA	5000 K 4000 K 3000 K 2700 K Red Green Blu RGB	Diffused

500mA



EN 60598 2-2 EN 60598 2-13

### ACCESSORI / ACCESSORIES

30500013	Controcassa / Outer casing
330002100	Alimentatore per max 3pz / Power supply for max 3 pcs
330002200	Alimentatore per min 4pz - max 12pz / Power supply for 4-12 pcs
307500010	Cavo neoprene 2x0,5 / Neoprene cable 2x0.5
307500020	Connettore IP68 / IP68 connector
307500027	Interruzione cavo 2 poli sistema NO-W / NO-W system, 2 pole cable interrupting
307500041	Sistema NOW con convertitore 24Vdc - 500mA / NOW System with 24vdc - 500mA converter

### SOLO PER VERSIONE RGB / ONLY FOR RGB VERSION:

330004800	Centralina PUSH per max 4pz / PUSH control unit for max 4pcs
-----------	--