

# SILO RGB

Sistemi lineari / Linear systems



2006/95/CE -- 2002/95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1 -- EN 62471 -- EN 62031

## Applicazione

Soffitto / Parete

Profilo lineare IP40 con 60 led/m da 0,24W RGB.

Estruso in lega di alluminio e copertura frontale di protezione in policarbonato.

Installazione a soffitto o parete con apposite clip di fissaggio.

Effetto luce uniforme

Realizzato su misura con lunghezza massima 2m.

Fornito con 1m di cavo 4x0,5.

Unità di alimentazione non compresa.

## Application

Ceiling / wall

Linear lamp RGB IP40 with 60x0,24W LEDs/m

Extruded aluminum alloy body with polycarbonate front protection

Ceiling or wall installation with clips provided

Uniform light effect


Customised length of max 2m

Provided with 1m of 4x0,5 cable

Power supply unit not included



## Silo IP65 RGB



### INCLUDED



Codice/Cod: **3173**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS	LUNGHEZZA LENGHT
Lineare / Linear	Anodized	RGB	Diffused Transparent	(max 2000)
00	4	9	0 9	

24Vdc 0,42/m IP 65 650°

### ACCESSORI / ACCESSORIES

330000400	Centralina RGB + telecomando per max 20m / RGB control unit with remote controller for max 20m
330007100	Alimentatore 24vdc max 150w / 150w 24vdc power supply