

JETRO ADJ 14,4W/m RGB IP65


Sistemi lineari / Linear systems



KELVIN	nm	LUMEN EFFETTIVI / REAL OUTPUT	CLASSE ENERGETICA / ENERGY CLASS
R	625	~ 108/m	G
G	525	~ 279/m	G
B	470	~ 55/m	G



Jetro Adj 14,4W/m RGB IP65



Codice/Cod: **3076** ■■■ ■■■ ■■■ ■■■ ■■■ ■■■ ■■■ ■■■

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS	LUNGHEZZA LENGHT
Lineare / Linear	Anodized ■ ANODIZED Black ■ RAL 9005	RGB	Diffused Transparent	(max 2000)
00	4 6	9	0 9	- - - -

ACCESSORI / ACCESSORIES

33000400	Centralina RGB + telecomando per max 20m / RGB control unit with remote controller for max 20m
330003300	(Vin 220/240Vac) 24Vdc - 20W
330003400	(Vin 220/240Vac) 24Vdc - 60W
330003500	(Vin 220/240Vac) 24Vdc - 35W
330003100	(Vin 220/240Vac) 24Vdc - 100W
330007100	(Vin 220/240Vac) 24Vdc - 150W
33000400	RGB controller con telecomando - RGB controller with remote control.

Descrizione / description

Lineare per esterni 14.4W/m. Disponibile con staffe orientabili e staffe a 45°. Corpo in alluminio anodizzato o verniciato e schermo in resina opale o trasparente. Disponibili nella temperatura colore RGB. MacAdam Step 2. Emissione luce diffusa. Forniti con 1m di cavo. Durata L80 B20 a 100.000h Ta (temperatura ambiente) 25°. Alimentatore da ordinare separatamente.

Linear profile for outdoor use 14.4W/m. Available with adjustable brackets and 45° brackets. Body in anodized or painted aluminum and diffuser in opal or transparent resin. Available in color temperature RGB. MacAdam Step 2. Diffuse light emission. Supplied with 1m cable. Lifespan L80 B20 at 100.000h Ta (ambient temperature) 25°. Ballast to be ordered separately.