

KION 6W RGB IP40

Incassi / Recess spotlights




KELVIN	nm	LUMEN EFFETTIVI / REAL OUTPUT	CLASSE ENERGETICA / ENERGY CLASS
R	620	~ 50	G
G	520	~ 65	G
B	465	~ 25	G


2006/95/CE -- 2002 /95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1
EN 60598-2-2 -- EN 62471 -- EN 62031



Kion 6W RGB flat surface



INCLUDED



Codice/Cod: **3147** ■■■ ■■■ ■■■ ■■■

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Raso / Trimless	PMMA <input type="checkbox"/> OPAL PMMA	RGB	Diffused
30	0	9	0

ACCESSORI / ACCESSORIES

305000013	Controcassa / Outer casing
330004800	Centralina PUSH per max 4pz / PUSH control unit for max 4pcs

Descrizione / description

Faretto da incasso a soffitto e pavimento IP40, potenza 6W. Installazione con controcassa su muratura. Flangia a filo pavimento / soffitto (solo tondo), in PMMA, corpo in alluminio anodizzato nero. Finitura della flangia PMMA satinata. Disponibili nella temperatura colore RGB, MacAdam Step 2. Ottica diffusa. Forniti con 150mm di cavo. Durata L80 B20 a 100.000h Ta (temperatura ambiente) 25°. Alimentatore da ordinare separatamente

Ceiling and floor recessed spotlights IP40, wattage 6W. Installation with housing box in masonry. Flange flush floor/ceiling (round only), made of PMMA, housing made of black anodized aluminum. PMMA flange in satin finish. Available in color temperature RGB, MacAdam Step 2. Diffuse optics. Versions are supplied with 150mm cable. Service life L80 B20 at 100.000h Ta (ambient temperature) 25°. Power supply must be ordered separately.