

# KION 6W RGB IP66

Incassi calpestabili / Recess walk-over spotlights





KELVIN	nm	LUMEN EFFETTIVI / REAL OUTPUT	CLASSE ENERGETICA / ENERGY CLASS
R	620	~ 50	G
G	520	~ 65	G
B	465	~ 20	G

2006/95/CE -- 2002 /95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1  
EN 60598-2-2 -- EN 62471 -- EN 62031



## Kion 6W versione con molle / with springs



Codice/Cod: **3157**    \*\*\*    \*\*\*    \*\*\*    \*\*\*

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round <b>10</b>	PMMA <input type="checkbox"/> OPAL PMMA	RGB	Diffused
Quadrato / Square <b>20</b>			

### ACCESSORI / ACCESSORIES

<b>330004800</b>	Centralina PUSH per max 4pz / PUSH control unit for max 4pcs
<b>307500013</b>	Cavo neoprene 6x0,5mm <sup>2</sup> . / Neoprene cable 6x0.5

## Descrizione / description

Faretto da incasso a soffitto e pavimento IP66, potenza 6W. Installazione con molle su controsoffitti. Disponibile con flangia tonda e quadrata. Flangia in PMMA, corpo in alluminio anodizzato nero. Finitura della flangia PMMA satinata. Disponibili nella temperatura colore RGB, MacAdam Step 2. Ottica diffusa. Fornite con 1m di cavo neoprene sezione 6x0,5mm. Durata L80 B20 a 100.000h Ta (temperatura ambiente) 25°. Alimentatore da ordinare separatamente

Ceiling and floor recessed spotlights IP66, wattage 6W. Installation with springs in false ceilings. Available with round and square flange. Flange made of PMMA, housing made of black anodized aluminum. PMMA flange in satin finish. Available in color temperature RGB, MacAdam Step 2. Diffuse optics. Supplied with 1m neoprene cable with 6x0.5mm cross-section. Service life L80 B20 at 100.000h Ta (ambient temperature) 25°. Power supply must be ordered separately.