

NICEA MINI 2,1W

Incassi calpestabili / Recess walk-over spotlights




KELVIN	CRI	LUMEN EFFETTIVI / REAL OUTPUT	CLASSE ENERGETICA / ENERGY CLASS
2700	90	~ 40	G
3000	90	~ 40	G
4000	80	~ 50	G

2006/95/CE -- 2002/95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1
EN 60598-2-2 -- EN 60598 2-13 -- EN 62471 -- EN 62031



Nicea Mini 2,1W



Codice/Cod: **3167**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round	Grey Black Inox	4000 K 3000 K 2700 K Red Green Blu	Side

ACCESSORI / ACCESSORIES

30500012	Controcassa / Outer casing
330010000	(Vin 220/240Vac) 700mA - 7.7W - IP20
330009700	(Vin 220/240Vac) 700mA - 10W - IP20
330009500	(Vin 220/240Vac) 700mA - 14W - IP67
330009900	(Vin 220/240Vac) 700mA - 30W (min 14W) - IP67
330007800	(Vin 220/240Vac) 700mA - 20W (min 7W)
330007200	(Vin 220/240Vac) 700mA - 28W (min 2W) - Dimmer Push, 0-10, 1-10, DALI
307500010	Cavo Neoprene 2X0,5 / Neoprene cable 2x0.5
307500020	Connettore IP68 / IP68 connector
307500027	Interruzione cavo 2 poli sistema NO-W / NO-W system, 2 pole cable interrupting
307500044	Sistema NOW con convertitore 24Vdc - 700mA / NOW System with 24vdc - 700mA converter

Descrizione / description

Faretti segnapasso da incasso a pavimento carrabili IP66, potenza 2.1W per emissione. Installazione con controcassa su muratura. Disponibile con flangia tonda in alluminio o acciaio, corpo in alluminio anodizzato. Finitura ottenuta mediante anodizzazione. Disponibili nelle temperature colore 2700K - CRI90 / 3000K - CRI90 / 4000K - CRI80, MacAdam Step 2. Ottica radiale (emissione laterale) con finestra a 100°. Forniti con 1m di cavo neoprene sezione 2x0.5mm. Durata L80 B20 a 100.000h Ta (temperatura ambiente) 25°. Versione con alimentatore da ordinare separatamente.

IP66 drive-on recessed spotlights, wattages 2.1W per emission. Installation with counter casing on masonry. Available with round aluminium or steel flange, anodised aluminium body. Finish obtained by anodising. Available in colour temperatures 2700K - CRI90 / 3000K - CRI90 / 4000K - CRI80, MacAdam Step 2. All-round optics (lateral emission) with 100° emission. Supplied with 1m of 2x0.5mm section neoprene cable. Durability L80 B20 at 100.000h Ta (ambient temperature) 25°. Version with ballast to be ordered separately available.