

# KIRA 6,7W

Incassi / Recess spotlights





KELVIN	CRI	LUMEN EFFETTIVI / REAL OUTPUT	CLASSE ENERGETICA / ENERGY CLASS
2700	90	~ 530	F
3000	90	~ 670	F
4000	80	~ 700	E

2006/95/CE -- 2002 /95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1  
EN 60598-2-2 -- EN 62471 -- EN 62031



## Kira 6,7W



Foro: 54mm / Hole: 54mm

Codice/Cod: **3195**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round	White □ RAL 9010	4000 K	20°
Quadrato / Square	Black ■ RAL 9005 Inox ■ AISI 316 STEEL	3000 K 2700 K	40° 60° Diffused

### ACCESSORI / ACCESSORIES

<b>330010000</b>	(Vin 220/240Vac) 700mA - 7.7W - IP20
<b>330009700</b>	(Vin 220/240Vac) 700mA - 10W - IP20
<b>330009500</b>	(Vin 220/240Vac) 700mA - 14W - IP67
<b>330009900</b>	(Vin 220/240Vac) 700mA - 30W (min 14W) - IP67
<b>330007800</b>	(Vin 220/240Vac) 700mA - 20W (min 7W)
<b>330007200</b>	(Vin 220/240Vac) 700mA - 28W (min 2W) - Dimmer Push, 0-10, 1-10, DALI
<b>307500021</b>	Anti abbagliamento alveolare / Non dazzling system
<b>307500031</b>	Antiabbagliamento vetro mezzo nero - mezzo trasparente / Non dazzling system with half black and half clear glass
<b>307500032</b>	Antiabbagliamento vetro mezzo nero - satinato / non dazzling system with half black and half sanded glass

## Descrizione / description

Faretti da incasso a soffitto e pavimento IP40, potenza 6.7W. Installazione con molle su controsoffitti. Disponibile con flangia tonda e quadrata. Flangia in alluminio o acciaio, corpo in alluminio anodizzato nero. Finitura ottenuta mediante anodizzazione o verniciatura a polvere. Disponibili nelle temperature colore 2700K - CRI90 / 3000K - CRI 90 / 4000K - CRI80, MacAdam Step 2. Ottiche 20°/40°/60°/Diffuso. Versione fornita con 150mm di cavo. Durata L80 B20 a 100.000h Ta (temperatura ambiente) 25°. Alimentatore da ordinare separatamente.

Ceiling and floor recessed spotlights IP40, wattage 6.7W. Installation with springs on false ceilings. Available with round and square flange. Aluminium or steel flange, black anodised aluminium body. Finished by anodising or powder coating. Available in colour temperatures 2700K - CRI90 / 3000K - CRI 90 / 4000K - CRI80, MacAdam Step 2. Optical lenses 20°/40°/60°/Diffused. Version supplied with 150mm cable. Service life L80 B20 at 100.000h Ta (ambient temperature) 25°. Power supply ito be ordered separately.