

# KION 4,8W IP66

Incassi calpestabili / Recess walk-over spotlights





KELVIN	CRI	LUMEN EFFETTIVI / REAL OUTPUT	CLASSE ENERGETICA / ENERGY CLASS
2700	90	~ 290	G
3000	90	~ 340	G
4000	80	~ 350	G

2006/95/CE -- 2002 /95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1  
EN 60598-2-2 -- EN 60598 2-13 -- EN 62471 -- EN 62031



## Kion 4,8W IP66 versione con molle / with springs



Codice/Cod: **3214**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round	PMMA <input type="checkbox"/> OPAL PMMA	4000 K	Diffused
Quadrato / Square		3000 K	
		2700 K	

### ACCESSORI / ACCESSORIES

<b>330002100</b>	(Vin 220/240Vac) 500mA - 6W
<b>330008800</b>	(Vin 220/240Vac) 500mA - 10W
<b>330002200</b>	(Vin 220/240Vac) 500mA - 22W (min 6W)
<b>330006800</b>	(Vin 220/240Vac) 500mA - 14W - IP67
<b>330009800</b>	(Vin 220/240Vac) 500mA - 28W (min 14W) - IP67
<b>330007200</b>	(Vin 220/240Vac) 500mA - 23W (min 4.5W) - Dimmer Push, 0-10, 1-10, DALI
<b>307500010</b>	Cavo neoprene 2x0,5 / Neoprene cable 2x0.5
<b>307500020</b>	Connettore IP68 / IP68 connector
<b>307500027</b>	Interruzione cavo 2 poli sistema NO-W / NO-W system, 2 pole cable interrupting
<b>307500041</b>	Sistema NOW con convertitore 24Vdc - 500mA / NOW System with 24vdc - 500mA converter

## Descrizione / description

Faretto da incasso a soffitto e pavimento IP66, potenza 4.8W. Installazione con molle su controsoffitti. Disponibile con flangia tonda e quadrata. Flangia in PMMA, corpo in alluminio anodizzato nero. Finitura della flangia PMMA satinata. Disponibili nelle temperature colore 2700K - CRI 90 / 3000K - CRI 90 / 4000K - CRI80, MacAdam Step 2. Ottica diffusa. Fornite con 1m di cavo neoprene sezione 2x0.5mm. Durata L80 B20 a 100.000h Ta (temperatura ambiente) 25°. Alimentatore da ordinare separatamente

Ceiling and floor recessed spotlights IP66, wattage 4.8W. Installation with springs in false ceilings. Available with round and square flange. Flange made of PMMA, housing made of black anodized aluminum. PMMA flange in satin finish. Available in color temperatures 2700K - CRI 90 / 3000K - CRI 90 / 4000K - CRI80, MacAdam Step 2. Diffuse optics. Supplied with 1m neoprene cable with 2x0.5mm cross-section. Service life L80 B20 at 100.000h Ta (ambient temperature) 25°. Power supply must be ordered separately.